


PRS350 APPLICATOR

Tape Applicator System



The PRS350 is a custom built, semi automatic system for applying Rippatape® to carton packaging. Sited between the rotary sheer and slitter scorer, the integrated design comprises a platform and multiple application heads. The system is ideally suited to high volume users of Rippatape®.

PRODUCT INFORMATION

EASY SET UP

Up to ten applicators can be fitted to the cross beam and are easily adjusted across the web. Each head is easily accessible and can hold a reel containing up to 60Km of Rippatape®. Accurate setting is achieved via the integrated rule located on the upper surface of the beam.

VERSATILE

The PRS350 makes any combination of tape lay out possible. Initial lay on speeds of 100mpm are standard, increasing to production speeds of maximum 350mpm. Rapid changeovers are facilitated by a simple switch enabling automatic cut off and braking.

EXCELLENT CONTROL

Reelcontrol is via a dancing arm which manages tension and braking pressure. Lay on pressure can be controlled independently ensuring consistent performance even at high speeds.

SIMPLE TO INSTALL

The PRS350 can be fully integrated into any corrugating line. Supastrip Tapes specialists offer support from initial consultation, design, build, install and commissioning. Combinations of platform lay-outs and access stairways, with guarded walkways, are available to complete the system. Web following and clean cut modules and options are available upon request.

SPECIFICATIONS



Model

Used for

PRS350

Rippatape®

Area required

4 x 6 m² minimum for installation

Core Diameter

152mm

Maximum Speed

350m/min

Contact us for more information:

E: cs@supa-strip.com

www.supastrip.com

 Supastrip Tapes inc